



00/378819
08/907635

Attorney Docket No. 35.C10457
Date: January 27, 1995

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Inventors: ¹⁰⁰ MIYUKI ENOKIDA, ^{et al} ET AL.

For: ANIMATING IMAGE EDITING APPARATUS AND
ANIMATING IMAGE EDITING METHOD

Enclosed are:

- ☒ Specification and Claims.
- ☐ Oath or Declaration.
- ☒ Transmittal Letter Under 37 C.F.R. § 1.53 and M.P.E.P. § 601.01.
- ☒ SIX (6) sheets of formal drawings.
- ☐ An assignment of the invention to _____
- ☐ Certified copies of _____ priority application(s).
- ☐ Associate power of attorney.

The fee has been calculated as shown below:

CLAIMS AS FILED				
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE \$365/\$730
TOTAL CLAIMS	39-20	19	x \$11 \$22	\$ 418.00
INDEP. CLAIMS	9-3	6	x \$38 \$76	\$ 456.00
Fee for Multiple Dependent claims \$120/\$240				
			TOTAL FILING FEE -----	\$1,604.00

☐ *Verified Statement claiming small entity status is enclosed.

468080 SE 920680

☐ Charge \$_____ to Deposit Account No. 06-1205. A duplicate copy of the paper is enclosed.

☒ The Commissioner is hereby authorized to charge any fees under 37 C.F.R. 1.16 or 1.17 which may be required during the entire pendency of this application, or to credit any overpayment, to Deposit Account No. 06-1205. A duplicate copy of this paper is enclosed.

☒ A check in the amount of \$1,604.00 to cover the filing fee is enclosed.

☐ A check in the amount of _____ to cover the recordal fee is enclosed. A duplicate copy of this paper is enclosed.

☒ Applicants' undersigned attorney may be reached in our Washington, D.C. office by telephone at (202) 347-8100. All correspondence should continue to be directed to our below listed address.

John D. Mabade
Attorney for Applicants

Reg. No. 32513

FITZPATRICK, CELLA, HARPER & SCINTO
277 Park Avenue
New York, New York 10172
Facsimile: (212) 758-2982

F507\W86209\SDM\rm



- 1 -

11604-101 A
CFO 10457155
~~62/278819~~
907635

Animating Image Editing Apparatus and

Animating Image Editing Method

C1

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to animating image editing apparatus and animating image editing method for editing a coded animating image.

Related Background Art

10 Recently, coding methods of coding a digital animating image at a high compression ratio by using an interframe correlation have been standardized as international methods. There is an MPEG as a representative method. According to the MPEG, an
15 interframe correlation is maximally used, a motion compensation is performed with reference to frames before and after a frame to be coded, and after that, an interframe differential coding is executed. Fig. 5 shows an example of the MPEG coding. In the coding
20 frame types of the MPEG, I frame, P frame, and B frame have been coded as shown in the diagram. The I frame is the independent frame in an intraframe code and one frame is inserted per 15 frames. The P frame is a forward motion predictive frame and is an interframe
25 code for performing the motion compensation by referring to the one-preceding P frame or the I frame. The B frame is an interframe predictive code for

08907635-080897

performing the motion compensation by predicting from both directions of the P and I frames before and after the B frame. The motion compensation is performed on a unit basis of a block which is called a macro block

5 (MB) as shown in Fig. 6. The MB is a unit such that an animating image is digitized at a sampling ratio of 4 : 1 : 1 of Y (luminance component) and Cb and Cr (color difference components) and, after that, Y (16 × 16 pixels), Cb (8 × 8 pixels), and Cr (8 × 8
10 pixels) are set to a block. The motion compensation is executed in the B and P frames. Since the blocks having a strong correlation ^{have} ~~has~~ to be searched (vector search) on a macro block unit basis, there is a drawback such that the processes of a coding unit are
15 complicated as compared with those of a decoding unit. Particularly, when the coding is executed only by μ software, it is difficult to execute it in a real-time manner. It is, therefore, a present situation that only the decoding is performed by μ software. When the
20 coding unit is realized by μ hardware, there is a drawback such that the circuit scale is extremely large.

As another problem, there is a problem at the time of the edition. Fundamentally, since the
25 interframe difference is coded, it is difficult to perform a cut edition between arbitrary frames. For example, when an animating image is divided into two

08907635.080897

a

A

A

A

sequences at the position of (1) in Fig. 5, there is a drawback such that the last frame cannot be decoded in the preceding sequence and the frames up to the next I frame cannot be decoded in the later sequence.

5 As a first method of solving the foregoing problems, there is a method of decoding all of the coded frame images and editing the decoded frame images after that.

10 The above method, however, has a drawback such that a memory of a large capacity is necessary to once accumulate the images after they were decoded.

15 In the above method, there is also a problem such that since all of the frame images need to be decoded irrespective of a fact such that the frame to be edited is a part of animating image and the decoded images are again encoded to accumulate them after that, the image deterioration is large.

20 As a second method of solving the foregoing problems, there is also an animating image processing apparatus using the intraframe coding method. For instance, there is a motion JPEG in which the JPEG system which is a coding of a color still image is independently applied to each frame of an animating image. In case of the motion JPEG, since the coding is also the intraframe coding, it is not so complicated as 25 in the MPEG and a frame edition can be also freely performed. However, since the interframe correlation

08907635-080897

is not used, there is a drawback such that a compression efficiency is remarkably worse than that of the interframe coding.

5 SUMMARY OF THE INVENTION

It is an object of the invention to provide an animating image editing apparatus and an animating image editing method which can solve the foregoing drawbacks.

10 It is another object of the invention to provide an animating image editing apparatus and an animating image editing method which do not require a memory of a large capacity when an editing process of coded animating image data is executed.

15 According to a preferred embodiment of the invention, the above objects are accomplished by an animating image editing apparatus comprising decoding means for decoding coded animating image data, storing means for intraframe coding the decoded animating image data and storing, editing means for decoding the
20 intraframe coded image stored in the storing means and for performing an arbitrary edition to the image, and coding means for coding the edited frame image by an animating image coding method.

25 Still another object of the invention is to provide an animating image editing apparatus and an animating image editing method in which an amount of

08907635.080697

image data to be decoded is extremely suppressed when an editing process is performed for a predetermined frame.

Another
A ~~Further another~~ object of the invention is to
5 provide an animating image editing apparatus and an
animating image editing method in which *inputting* ~~input~~ an
animating image data can be coded at a high speed and
an image can be compressed at a high compression after
edition.

Another
A ~~Further another~~ object of the invention is to
10 provide an animating image editing apparatus and an
animating image editing method which can easily and
promptly edit an animating image.

Another
A ~~Further another~~ object of the invention is to
15 provide an animating image editing apparatus and an
animating image editing method which can edit an
interframe coded ~~an~~ animating image while minimizing a
deterioration of a picture quality.

Another
A ~~Further another~~ object of the invention is to
20 provide an animating image editing apparatus and an
animating image editing method having a novel function.

The above and other objects and features of the
present invention will become apparent from the
following detailed description and the appended claims
25 with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram showing the first embodiment;

Fig. 2 shows an example of a display picture plane for edition;

5 Fig. 3 is a diagram showing the second embodiment;

Fig. 4 shows an example such that an intraframe coding was performed to a part of a sequence;

10 Fig. 5 is a diagram showing a state of a sequence when an interframe coding is performed;

Fig. 6 is a diagram showing a macro block;

Fig. 7 is a block diagram showing a constructional outline of a system according to the fourth to sixth embodiments;

15 Fig. 8 is a block diagram of a main section of the fourth embodiment;

Fig. 9 is an explanatory diagram of the fifth embodiment;

20 Fig. 10 is a block diagram of a main section of the fifth embodiment; and

Fig. 11 is a block diagram of a main section of the sixth embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 <First embodiment>

Fig. 1 is a block diagram of the first embodiment. Reference numeral 1 denotes a video camera

08907635 080897
/68080" 5E9/0680

for inputting an animating image; 2 a capture board unit for forming each frame of the animating image; 3 a JPEG codec unit for performing intraframe coding and decoding (processing a program by a CPU 9); 4 a disk
5 for accumulating animating images; 5 a video RAM unit for outputting the decoded animating image to a display 7; 6 an MPEG codec unit for coding/decoding an interframe coded animating image (processing a program by the CPU 9); 9 the CPU to control the apparatus. An
10 animating image to be processed is inputted from the video camera 1 and is digitized by the video capture board unit. Reference numeral 19 denotes an operation unit including a mouse, or a pointer, which will be described hereinlater. In the embodiment, (360 pixels
15 x 240 lines) construct one frame and digital animating images of 30 frames per second are formed. As pixel signals, the Y, Cb, Cr signals obtained by the sampling at the sampling ratio of (4 : 1 : 1) which is performed by the MPEG or the like are used. The Y, Cb, and Cr
20 signals formed by the capture board unit 2 are coded in the frame by the JPEG codec unit 3 through a computer bus 8 in a real-time manner. The coding is executed by the JPEG system by regarding each frame as a still
25 system has been well-known, the description is omitted here. The coded animating images of 30 frames/second are stored into the disk 4 through the computer bus 8

08907635-080897
268080-5920680

in a real-time manner. In parallel with the coding,
the digital animating images formed by the capture
board unit 2 are sent to the video RAM unit 5 and are
converted to the RGB signals for displaying the
5 animating images and, after that, the images are
displayed by the display 7 in a real-time manner. By
the processes as mentioned above, while the animating
image inputted from the video camera 1 is displayed by
the display 7 in a real-time manner, the image is coded
10 by the JPEG codec unit 3 and the coded data is stored
into the disk 4. The input of the animating image to
the disk 4 is continued until one animating image scene
(hereinafter, referred to as a sequence) is finished.
One sequence after completion of the input is
15 reproduced on the display 7 as necessary. The
reproducing process is performed as follows. Codes of
one sequence are sequentially read out on a frame unit
basis and are sent to the JPEG codec unit 3 which can
perform the coding at a speed higher than that in the
20 MPEG through the computer bus 8 and are decoded. The
decoded frames are sequentially transferred to the
video RAM unit 5 on the frame unit basis as Y, Cb, and
Cr signals of (360 pixels x 240 lines) and are
displayed by the display 7 in a manner similar to the
25 case of the foregoing real-time animating image input
display (hereinafter, such an operation is called as a
normal reproduction).

08907635-080897

When one animating image sequence is inputted, generally, unnecessary portions are often included at the positions before and after or in the halfway of the sequence. According to the embodiment, therefore, the editing process is performed by using a feature of the intraframe coding such that each frame is independent.

Fig. 2 shows an example of edition. Reference numeral 7 denotes the display in which an edition window 10 is displayed. In the edition window 10, each frame of the sequence of the decoded animating image is displayed in a reduced size. As for the reduction, a normal method of simply thinning out is used and a resolution is decreased to a value such that the contents can be known, thereby enabling a few frames to be simultaneously displayed. Reference numeral 15 indicates a frame as a target point at the time of the edition. Reference numeral 14 denotes a one-preceding frame; 13 a two-preceding frame; 12 a three-preceding frame; 16 a one-later frame; 17 a two-later frame; and 18 a three-later frame.

In case of the normal reproduction, a frame of a size of (360 pixels x 240 lines) is displayed in another window (not shown). At the time of the edition reproduction, however, since a plurality of frames before and after the target frame are displayed as mentioned above, the pixels reduced to about $(1/4 \times 1/4)$ are reproduced. In the edition reproduction, the

frame 15 is set to a reproduction point and the frames before and after such a frame are moved and displayed as shown by an arrow. The frames are displayed in a normal speed mode, a slow speed mode, sequential frame display mode, or the like as necessary. Reference numeral 11 denotes an edition tool bar for cutting unnecessary frames and for selecting only necessary frames. Fig. 2 shows a state in which the frames 13 to 17 are selected (bars of the hatched portions) by a mouse or a pointer. In this case, the frames before the frame 12 and the frames after the frame 18 are unnecessary portions. The frames other than the necessary portions selected as mentioned above are deleted and edited from the disk 4. Since the code data stored in the disk 4 are the intraframe coded data, it can be easily edited. In the embodiment, the editing process is executed by the CPU 9 in a software manner. The edited code data can be confirmed by performing the normal reproduction as mentioned above.

The editing process mentioned above is performed on the basis of the intraframe code data which can be easily edited. After the edition, the intraframe code is converted to the interframe code having a compression efficiency higher than that of the intraframe code and the animating image is efficiently restored to the disk 4. One sequence of the edited intraframe codes stored in the disk 4 is read out every

frame and is decoded by the JPEG codec unit 3 in a manner similar to the normal reproduction. Since there is no need to again convert the intraframe code to the interframe code in a real-time manner, however, it is sufficient for the JPEG codec unit 3 to decode in accordance with the speed of the interframe coding. In the embodiment, the MPEG system is used to again encode the decoded animating image to the interframe coded frame image. Since the re-encoding is performed by software by the CPU 9, it is executed by an idle time of the CPU.

According to the MPEG coding, as shown in Fig. 5, the data is interframe/intraframe coded into three kinds of frame types of I, P, and B frames. The coded frames are again sequentially stored into the disk 4 in accordance with the order from the frame after completion of the coding and the above operation is continued until the end of the sequence, thereby finishing the re-encoding. After that, by deleting an unnecessary sequence of the intraframe codes, it is converted to the sequence in which the compression efficiency is improved so that the disk 4 is efficiently used.

As mentioned above, the animating image sequence which was re-encoded to the interframe codes is sequentially decoded by an MPEG codec 6 as necessary and can be also similarly produced to the display 7 via

the video RAM unit 5.

As mentioned above, the input of the animating image is coded by the intraframe coding in a real-time manner, so that the coding can be easily performed with a small circuit scale as compared with the case of using the interframe coding by the MPEG. By using the intraframe code, the animating image can be easily edited. By converting the intraframe code to the interframe code of a good compression efficiency after the edition, the animating image process such that the input edition of the animating image is easy and the compression efficiency is high is realized.

<Second embodiment>

Fig. 3 is a diagram showing the second embodiment. The second embodiment relates to a case where animating images have already been converted to digital codes and stored in a CD-ROM or the like. In Fig. 3, reference numeral 20 denotes a CD-ROM player which is connected to the computer bus 8 by an SCSI bus. In Fig. 3, the same component elements as those in Fig. 1 are designated by the same reference numerals. The CD-ROM player 20 is an animating image reading apparatus for displaying animating image data generally stored in the CD-ROM onto the display 7. Codes are read out from the CD-ROM player 20 at a predetermined bit rate. It is generally desirable that such a kind of animating images for accumulation have

been interframe coded from a view point of the compression efficiency. In the second embodiment, a case where the animating image coded by the MPEG system is read out from the CD-ROM will be described. Codes of one sequence read out from the CD-ROM player 20 are decoded by the MPEG codec 6 via the computer bus 8 in a real-time manner. The frame images (360 pixels x 240 lines; Y, Cb, and Cr signals) sequentially decoded are again sequentially converted every frame to the JPEG codes as intraframe codes by the JPEG codec unit 3 through the computer bus 8. Simultaneously, the frame images decoded by the MPEG codec 6 are normally reproduced onto the display 7 via the video RAM unit 5. The sequence coded by the JPEG codec unit 3 is sequentially stored into the disk 4 by an amount corresponding to a sequence of a necessary length. After completion of the storage, as described in the first embodiment, the frame edition can be performed as necessary. It is also possible to again convert the intraframe code to the interframe code in order to raise the compression efficiency.

As mentioned above, while decoding the interframe coded animating image, by re-encoding to the intraframe code, the edition on the frame unit basis can be promptly and easily performed.

<Third embodiment>

In the second embodiment, although the MPEG

08907635.080897

codes have been decoded and converted to the intraframe codes with respect to all of the sequences, only the neighboring frames to be edited can be also converted to the intraframe codes as follows. In Fig. 3, in a recording medium (the CD-ROM in the third embodiment) which can perform the optical recording, magnetic recording, or the like, the MPEG codes (interframe codes) stored in the CD-ROM are decoded by the MPEG codec 6 and only the display operation is performed. In this instance, the re-encoding by the JPEG codec unit is not executed. As for the display, the edition reproduction is performed as described in Fig. 2. As mentioned above, the necessary portions are designated by the edition tool bar 11. In the case where the editing portions have been interframe coded, however, the frame edition cannot be easily performed. Therefore, a partial intraframe coding conversion as shown in Fig. 4 is executed. As an interframe code, the I, P, and B frames are encoded every fifteen frames between the I frames by the MPEG encoding as described in Fig. 5.

For example, in case of cutting the portion of ① between the B frames in each of the second and third frames in Fig. 4, the last B frame of the previous sequence of the cut portion cannot be reproduced. In the later sequence, a state in which up

to the next I frame cannot be reproduced (broken link) occurs. In the embodiment, therefore, four frames between the P frames (between the I and P frames in case of the I frame) including the cut portion are
5 decoded and are again encoded to the I frame, so that the frame edition at an arbitrary position can be performed. Four frames including the portion to be cut in the sequence which was read out from the CD-ROM player 20 in Fig. 3 are decoded by the MPEG codec 6 and
10 can be also partially again encoded as an intraframe by the CPU 9 in an operational processing, i.e., a software manner. In place of again encoding to the intraframe in a software manner, the intracoding can be also performed by the JPEG codec 3. Instead of
15 decoding all the encoded frames, by partially again encoding to the intraframe code only frame images in minimum number including frame images indicated to be edited upon editing, in which the frames which are not edited can be reproduced later, as in the embodiment,
20 there is no need to again encode to the interframe code for the purpose of the improvement of a compression ratio after the edition. A deterioration of the picture quality can be also minimized to the portions before and after the edition.

25 <Fourth embodiment>

The fourth embodiment will now be described with respect to the case where the MPEG system is used as a

to the next I frame cannot be reproduced (broken link) occurs. In the embodiment, therefore, four frames between the P frames (between the I and P frames in case of the I frame) including the cut portion are
5 decoded and are again encoded to the I frame, so that the frame edition at an arbitrary position can be performed. Four frames including the portion to be cut in the sequence which was read out from the CD-ROM player 20 in Fig. 3 are decoded by the MPEG codec 6 and
10 can be also partially again encoded as an intraframe by the CPU 9 in an operational processing, i.e., a software manner. In place of again encoding to the intraframe in a software manner, the intracoding can be also performed by the JPEG codec 3. Instead of
15 decoding all the encoded frames, by partially again encoding to the intraframe code only frame images in minimum number including frame images indicated to be edited upon editing, in which the frames which are not edited can be reproduced later, as in the embodiment,
20 there is no need to again encode to the interframe code for the purpose of the improvement of a compression ratio after the edition. A deterioration of the picture quality can be also minimized to the portions before and after the edition.

25 <Fourth embodiment>

The fourth embodiment will now be described with respect to the case where the MPEG system is used as a

coding system of animating image coding data which is
inputted, the JPEG system is used as an intraframe
coding system that is used in the apparatus, all of the
frames of the animating image coding data which is
5 inputted are code converted, and an editing operation
is executed.

Fig. 7 is a constructional diagram of the
animating image editing apparatus of the embodiment.
Reference numeral 101 denotes a system bus to control
10 the whole system; 102 a code converting unit I for
decoding animating image coding data that is inputted
and for converting into the intraframe coding data; 103
an animating image editing unit for decoding the
internal coding data and for performing an animating
15 image edition; and 104 a code converting unit II for
again converting the result of the animating image
edition to the animating image coding data.

Fig. 8 shows a detailed block construction of
each processing unit. In the diagram, the same blocks
20 as those shown in Fig. 7 are designated by the same
reference numerals.

The code converting unit I (102) comprises three
blocks 120, 121, and 122. Reference numeral 120
denotes an MPEG decoder for decoding a bit stream which
25 is animating image coding data that is inputted and
which was encoded by the MPEG system; 121 denotes a
JPEG encoder for encoding the decoded frame image data

by the JPEG system as an intraframe code; and 122 a memory or file to store an output of the JPEG encoder 121.

5 The animating image editing unit 103 comprises five blocks 122, 124, 125, 126, and 122. Reference numeral 124 denotes a JPEG decoder; 125 an editing unit to edit the animating image on a frame unit basis; 126 a JPEG encoder to JPEG encode the image data edited by the editing unit 125 on the frame unit basis; and 122
10 the memory or file to store an output of the JPEG encoder 126.

The code converting unit 104 comprises two blocks 122 and 129. Reference numeral 129 denotes an MPEG encoder to encode by the MPEG system.

15 A processing procedure of the animating image editing apparatus of the fourth embodiment will now be described hereinbelow with reference to Fig. 8.

First, when the animating image coding data which has previously been stored in the memory or the like and encoded by the MPEG system is designated from
20 the user by using a pointing device such as a mouse or the like (not shown), the designated animating image coding data is sequentially decoded by the MPEG decoder 120 in the code converting unit 102 in accordance with
25 the order of the MPEG bit stream. Subsequently, the image data of every frame as an output result is inputted to the JPEG encoder 121 and is JPEG encoded on

468080" SE 9/0680

a frame unit basis and is stored into the memory or
file 122. The user retrieves an arbitrary frame to be
edited from the image data which was stored in the
memory or file 122 and was JPEG encoded, so that an
5 animating image editing process can be performed.

As an animating image edition, the frame
designated by the user is read out from the memory or
file 122 and is decoded by the JPEG decoder 124 and is
returned to the frame image. An editing operation is
10 executed by the editing unit 125 to the image data
returned to the frame image. The editing operation in
the embodiment denotes that the image data itself in
the frame is rewritten. The frame image after
completion of the editing operation is again encoded
15 every frame image by the JPEG encoder 126 in order to
store into the memory or file 122. When there are a
plurality of frames to be edited, the above editing
operation is repeated. After completion of the editing
operations of all of the frame images to be edited, the
20 coding data which was JPEG encoded every frame by the
code converting unit 104 is read out from the memory or
file 122. The animating image encoding is executed in
the MPEG encoder 129 by the MPEG system to all of the
frames.

25 According to the embodiment as mentioned above,
after the intraframe coding using the JPEG system was
performed to the input animating image coding data

encoded by the MPEG system, the picture plane to be
edited is retrieved and is subjected to the editing
process and the animating image encoding is again
executed. Thus, the animating image coding data can be
5 edited and the memory capacity can be remarkably
reduced as compared with that in case of decoding all
of the animating image coding data.

<Fifth embodiment>

The fourth embodiment has been described with
10 respect to the example in which after all of the image
data which had been animating image encoded by the MPEG
system was decoded, it is edited. The fifth embodiment
will be explained with respect to the case where only
the image data of the portions necessary for edition is
15 decoded from the image data which was animating image
encoded by the MPEG system and is subjected to the
editing process.

In the fifth embodiment, it is assumed that the
image data which was animating image encoded by the
20 MPEG system is intraframe encoded (intra-picture) every
15 frames. It is also assumed that 20 frames within a
range from the 20th frame to the 40th frame are used as
frames to which the user performs the editing process.

In this case, the image data which is inputted
25 and was animating image encoded by the MPEG system has
a construction as shown at 138 in Fig. 9. In the
diagram, reference numerals 130 to 134 denote positions

of the intra-picture in the image data which is inputted and was animating image encoded by the MPEG system. For example, the intra-picture 130 indicates the 0th frame. The next intra-picture 131 indicates the 15th frame. In case of the embodiment, since 20 frames (the 20th frame to the 40th frame) are edited, it is sufficient to decode and edit the data with a range from the intra-picture 131 to the intra-picture 133 in a bit stream 138.

10 A construction to execute the above processes will now be described with reference to Fig. 10.

 In the diagram, blocks which execute operations similar to those in the fourth embodiment are designated by the same reference numerals. In the diagram, reference numeral 140 denotes an intra-detector to detect a frame image as an intra-picture in the image data which was animating image encoded by the MPEG system.

 First, the bit stream 138 is inputted to the intra-detector 140. After that, the data within a range from the intra-picture 130 to the frame before the intra-picture 131, namely, to the 14th frame is outputted to a line 141 as an inputted bit stream and is stored into a predetermined file. When the code of the intra-picture 131 is detected, the frames of the intra-picture 131 and subsequent intra-pictures are outputted to a line 142 in order to perform the editing

process. The data of the bit stream outputted to the line 142 passes through the MPEG decoder 120 and JPEG encoder 121 and each frame is encoded by the JPEG system and is supplied to the memory or file 122. The intra-detector 140 outputs the signal to the line 142 until the code of the intra-picture 133 is detected. After the code of the intra-picture 133 was detected, the output is again returned to the line 141 and the subsequent bit stream is outputted to another file different from the above file.

Coding data 135 and 137 are filed as mentioned above without being subjected to the editing process.

Processes such that the user edits the 20 frames (the 20th to 40th frame) will now be explained.

The frames (the 15th to 44th frame) have been stored in the memory or file as coding data which was encoded by the JPEG system. The JPEG coding data within a range from the 20th frame to the 40th frame is read out from the memory or file 122 and is decoded by the JPEG decoder 124, so that the image data is formed.

After that, the frames (the 20th to 40th frames) are edited by the editing unit 125 and are JPEG encoded by the JPEG encoder 121 and are stored into the memory or file 122. After completion of the editing operation, the JPEG coding data is read out from the memory or file 122 and is decoded into the image data by the JPEG decoder 124. The image data is further

MPEG encoded by the MPEG encoder 129 and is outputted to a file or the like. The output result is filed as coding data 136 in Fig. 9.

5 The coding data 135, 136, and 137 are finally rearranged into a bit stream as one coding data by a CPU or the like (not shown), so that the edition of only the necessary frames which are desired by the user can be performed.

10 In the fifth embodiment, after completion of the animating image edition, the frames edited by the JPEG system are again encoded by the MPEG system. However, the invention is not limited to such a construction. It is also possible to construct as follows. Namely, the image data after the edition is stored into the
15 memory or file 122 without being JPEG encoded. Only the frames which are not subjected to the editing process, namely, only the frames (the 15th to 19th frames and the 41st to 44th frames) as JPEG codes are decoded by the JPEG decoder 124 in the embodiment. The
20 edited frames which are not encoded are directly outputted to the MPEG encoder without passing through the JPEG decoder 124.

25 With the above construction, when the animating image edition is executed to a predetermined frame, an amount of image data to be decoded can be reduced, so that the memory capacity to store the image data after it was decoded can be reduced. The time that is

08907635-080897
268080-5E920680

Consequently, the animating image edition can be executed at a high speed.

The above fifth embodiment has been described with respect to the case of using the JPEG system as an intraframe coding system. However, as shown in Fig. 11, the encoding process can be also performed by the intra-pictures in an MPEG chip. In the diagram, the component elements which execute the similar operations as those of the component elements in the fourth and fifth embodiments are designated by the same reference numerals.

The detailed operations are substantially the same as those in the fifth embodiment except that the portions which are stored into the memory or file 122 are the coding data of the intra-pictures of the MPEG. Therefore, the description of the operation principle is omitted here.

25 Although the MPEG system has been used as an
animating image coding system of the input in the sixth
embodiment, the invention is not limited to such a

system but can be also obviously applied to the H261 system or, further, to another animating image coding system.

5 Although the internal coding system has been described with respect to the JPEG system and the intra-pictures of the MPEG, the invention is not limited to them but can be also applied to any system so long as it is the intraframe coding system.

10 Although the embodiments have been described with respect to the example in which the image in the frame is changed as an animating image edition, the invention is not limited to such an edition. It is also possible to change the number of frames or to execute an editing operation in the time base direction
15 such as extraction of frames, insertion of frames, or the like.

It will be also obviously understood that the animating image coding data is communicated from external communicating means in a real-time manner.

20 When the image data stored in the memory or file 122 is edited, the image of only the low frequency component is decoded from the image data of one frame and is displayed on a monitor (not shown), thereby deciding the edition image by using the image of a low
25 resolution. After that, all of the images of one frame are displayed and are subjected to the actual editing process. Thus, the editing process can be performed at

08907635 080897
/68080" 559/0880

a high speed.

As described above, according to the embodiments
4 to 6, the animating image data which was encoded by
the animating image coding system using the interframe
5 correlation is once encoded by the intraframe coding
system and is animating image edited and is again
encoded by the animating image coding system. Thus,
the animating image data of the coding data which
cannot be directly animating image edited so far can be
10 edited. The capacity of the image memory that is
needed during the editing operation can be remarkably
reduced.

Further, since the amount of animating image
data to be decoded when a predetermined frame is edited
15 can be decreased, the memory capacity can be saved and
the processes can be executed at a high speed.

The present invention is not limited to the
foregoing embodiments but many modifications and
variations are possible within the spirit and scope of
20 the appended claims of the invention.

08907635-080897
68080-5270580

WHAT IS CLAIMED IS:

Sub A1 1. An animating image editing apparatus comprising:
decoding means for decoding encoded animating
image data;
5 storing means for intraframe coding and storing
said decoded animating image data;
editing means for decoding the images which were
stored in said storing means and were intraframe
encoded and for performing an arbitrary edition; and
10 coding means for coding said edited frame image
by an animating image coding system.

the
2. An apparatus according to claim 1, wherein ^{the} said
moving
15 encoded ~~animating~~ image data is transmitted from an
external apparatus ~~by a communication~~.

the
3. An apparatus according to claim 1, wherein ^{the} said
editing comprises editing
arbitrary ~~edition is an edition~~ in one frame or an
editing
20 ~~edition~~ in a time base direction between frames.

Sub A2 4. An apparatus according to claim 1, further
including display means,
wherein said decoding means decodes a part of
said animating image data in the encoded animating
25 image data and displays to display means.

5. An animating image editing apparatus comprising:

08607635.080897
768080.58970680

A
A
A

A
D
D

intraframe detecting means for detecting an intraframe in encoded animating image data;

decoding means for decoding the animating image data of a predetermined number of frames after the frame detected by said intraframe detecting means;

storing means for storing the animating image data decoded by said decoding means on a frame unit basis;

editing means for performing an arbitrary edition to the images of the frame unit stored in said storing means; and

coding means for encoding said edited frame images by an animating image coding system.

6. An apparatus according to claim 5, further including intraframe coding means,

wherein after said decoded animating image data is intraframe encoded by said intraframe coding means, said storing means stores the intraframe coded animating image data.

7. An apparatus according to claim 5, wherein ^{the} said encoded ^{moving} animating image data is transmitted from an external apparatus ~~by a communication.~~

8. An apparatus according to claim 6, wherein ^{the} said encoded ^{moving} animating image data is transmitted from an

08907635.08089

A
A
A

A
A

A
A
external apparatus ~~by a communication.~~

9. An apparatus according to claim 5, wherein ^{the} said
arbitrary edition is an edition in the frame or an
5 edition in a time base direction between frames.

A
10. An apparatus according to claim 6, wherein ^{the} said
arbitrary edition is an edition in the frame or an
edition in a time base direction between frames.

10
11. An apparatus according to claim 5, wherein said
decoding means executes the decoding from the
intraframe just before the frame to be edited by said
editing means.

15
12. An apparatus according to claim 6, wherein said
decoding means executes the decoding from the
intraframe just before the frame to be edited by said
editing means.

20
Sub A³ 13. An apparatus according to claim 5, wherein said
decoding means decodes a part of said animating image
data in the encoded animating image data and displays
to display means.

25
14. An animating image editing apparatus
comprising: *a*

first encoding means for encoding inputted
animating image data by a coding method which pays an
importance to a speed;

memory means for storing said animating image
5 data encoded by said first encoding means;

editing means for editing said encoded animating
image data; and

second encoding means for encoding said edited
animating image data by a coding method which pays an
10 importance to a compression ratio than said first
encoding means.

15. An apparatus according to claim 14, wherein
said second encoding means executes the encoding
15 including an interframe encoding.

16. An apparatus according to claim 14, wherein
said first encoding means executes an intraframe
encoding.

20 17. An apparatus according to claim 14, wherein
said edition is an edition on a frame image unit
constructing said animating image data.

25 18. An apparatus according to claim 14, wherein
said first encoding means executes a coding process to
the input of said animating image data in a real-time

08907635.080897

manner.

19. An apparatus according to claim 14, further
including display means for displaying said animating
5 image data and instructing means for instructing the
edition to said editing means,

wherein said editing means executes said edition
in accordance with the instruction from said
instructing means on said display means.

10

20. An apparatus according to claim 19, wherein
said display means multi-screen displays said animating
image data as a plurality of frame images.

21. An apparatus according to claim 20, wherein
said multi-screens are images obtained by reducing the
frame images included in said animating image data.

22. An apparatus according to claim 19, wherein
20 said edition denotes that the animating image data
which is stored and encoded in said memory means is
edited in accordance with the instruction of said
instructing means.

23. An apparatus according to claim 14, wherein
25 said first and second encodings are executed on the
basis of a coding conversion program.

20250801 09:59:00

24. An animating image editing apparatus
comprising:

decoding means for decoding animating image data
encoded by an encoding method including an interframe
5 encoding;

encoding means for encoding the animating image
data decoded in parallel with the decoding by said
decoding means by an intraframe encoding; and

editing means for editing said encoded animating
10 image data on a frame unit basis.

25. An apparatus according to claim 24, further
including display means for displaying ^{the} ~~said~~ decoded
^{moving} ~~animating~~ image data.

26. An apparatus according to claim 24, further
including memory means for storing ^{the} ~~said~~ edited
^{moving} ~~animating~~ image data.

E

27. An apparatus according to claim 24, further
including accumulating means for accumulating the
^{moving} ~~animating~~ image data encoded by an encoding method
including ^{the} ~~said~~ interframe encoding.

28. An apparatus according to claim 24, wherein
^{the} ~~said~~ encoding and ^{the} ~~said~~ decoding are executed on the
basis of a conversion program.

Sub 29
29. An animating image editing apparatus
comprising:

decoding means for decoding animating image data
which was encoded by an encoding method including an
5 interframe encoding and stored in a memory medium;

display means for displaying said decoded
animating image data;

instructing means for giving an editing
instruction to the animating image data displayed on
10 said display means; and

encoding means for intraframe encoding the frame
images of the minimum number which are necessary to
decode the animating image data instructed by said
instructing means in the animating image data stored in
15 said memory medium.

A
30. An apparatus according to claim 29, wherein
the ~~said~~ encoding and *the* ~~said~~ decoding are executed on the
basis of a conversion program.

A
A
31. An apparatus according to claim 29, wherein
the ~~said~~ editing process is a cutting process of *E* ~~said~~
moving ~~animating~~ image data.

A
32. An apparatus according to claim 29, wherein the
encoding including *the* ~~said~~ interframe encoding is an MPEG.

33. An apparatus according to claim 29, wherein said display means multi-screen displays, ^{the moving} ~~said animating~~ image data as a plurality of frame images.

5 , 34. An apparatus according to claim 33, wherein

~~said multi-screens are images which are obtained by
reducing the frame images included in ^{the moving} said animating
image data.~~

10 *uh* 35. An apparatus according to claim 29, wherein
said minimum number of frame images include the frame
images instructed by said instructing means and are
images of the number of frames such that said animating
image data can be decoded without a broken link.

15

4 → 36. An animating image editing method comprising the steps of:

```
decoding encoded animating image data;
```

intraframe encoding and storing said decoded

```
20     animating image data;
```

decoding an image which is stored in said
storing step and is intraframe encoded and performing
an arbitrary edition; and

encoding said edited frame images by an
25 animating image encoding system.

37. An animating image editing method comprising

the steps of:

intraframe detecting an intraframe in encoded
animating image data;

5 decoding the animating image data of a
predetermined number of frames after the frame detected
by said intraframe detecting step;

storing the animating image data decoded by said
decoding step on a frame unit basis;

10 performing an arbitrary edition to the images of
the frame unit stored in said storing step; and

encoding said edited frame images by an
animating image encoding system.

38. An animating image editing method comprising
15 the steps of:

first encoding inputted animating image data by
an encoding method which pays an importance to a speed;

storing said animating image data encoded by
said first encoding step;

20 editing said encoded animating image data; and

second encoding said edited animating image data
by an encoding method which pays an importance to a
compression ratio than said first encoding step.

25 39. An animating image editing method comprising
the steps of:

decoding animating image data encoded by an

encoding method including an interframe encoding;

encoding the animating image data decoded in parallel with the decoding by said decoding step by an intraframe encoding; and

5 editing said encoded animating image data on a frame unit basis.

Add E'

Add G_4

Add H_3

08907634 080897

FIG. 1




FIG. 2




FIG. 3





FIG. 4



BY	O.G. FIG.	
	CLASS	SUBCLASS
DRAFTSMAN		

4630810-5204810

FIG. 5




FIG. 6






FIG. 7





468030 "GE9206"		O.G. FIG.	
BY	CLASS	SURCLASS	
CRAFTSMAN			






FIG. 9

FIG. 10



468030 "SEE 3/06"		O.G. FIG.	
BY	CLASS	SUBCLASS	
DRAFTSMAN			

FIG. 11



**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**



As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled ANIMATING IMAGE EDITING APPARATUS AND ANIMATING IMAGE EDITING METHOD the specification of which

☐ is attached hereto. ☒ was filed on January 27, 1995 as Application Serial No. 08/378,819

and was amended _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Country	Application No.	Filed (Day/Mo./Yr.)	Priority Claimed (Yes/No)
JAPAN	6-010083	31 January 1994	YES
JAPAN	7-007389	20 January 1995	YES

I hereby appoint Joseph M. Fitzpatrick (Registration No. 17,398), Lawrence E. Scinto (Registration No. 18,973), William J. Brunet (Registration No. 20,452), Robert L. Baechtold (Registration No. 20,860), John A. O'Brien (Registration No. 24,367), Nels T. Lippert (Registration No. 25,888), John A. Krause (Registration No. 24,613), Henry J. Renk (Registration No. 25,499), Peter Saxon (Registration No. 24,947), Anthony M. Zupcic (Registration No. 27,276), Charles P. Baker (Registration No. 26,702), Stevan J. Bosses (Registration No. 22,291), Edward E. Vassallo (Registration No. 29,117), Ronald A. Clayton (Registration No. 26,718), Lawrence A. Stahl (Registration No. 30,110), Laura A. Bauer (Registration No. 29,767), Leonard P. Diana (Registration No. 29,296), David M. Quinlan (Registration No. 26,641), Nicholas N. Kallas (Registration No. 31,530), William M. Wannisky (Registration No. 28,373), Lawrence Alaburda (Registration No. 31,583), Lawrence S. Perry (Registration No. 31,865), Robert H. Fischer (Registration No. 30,051), Christopher Philip Wrist (Registration No. 32,078), Gary M. Jacobs (Registration No. 28,861), Michael K. O'Neill (Registration No. 32,622), Bruce C. Haas (Registration No. 32,734), Scott K. Reed (Registration No. 32,433), Scott D. Malpede (Registration No. 32,533), John A. Mitchell (Registration No. 19,032), Fredrick M. Zullo (Registration No. 32,452), Richard P. Bauer (Registration No. 31,588), Eric B. Janofsky (Registration No. 30,759), Warren E. Olsen (Registration No. 27,290), Abigail F. Cousins (Registration No. 29,292), Alan W. Fiedler (Registration No. 33,690), Jennifer A. Tegfeldt (Registration No. 31,310), Steven E. Warner (Registration No. 33,326), Thomas J. O'Connell (Registration No. 33,202), Aaron C. Deditch (Registration No. 33,865), Penina Wollman (Registration No. 30,816), David L. Schaeffer (Registration No. 32,716), Jack S. Cubert (Registration No. 24,245), Mark A. Williamson (Registration No. 33,628), John T. Whelan (Registration No. 32,448), Patricia M. Drost (Registration No. 29,790), Jean K. Dudek (Registration No. 30,938), Raymond R. Mandra (Registration No. 34,382) and Dominick A. Conde (Registration No. 33,856), my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Address all correspondence to:

FITZPATRICK, CELLA, HARPER & SCINTO

277 Park Avenue

New York, N.Y. 10172

Telephone No. (212) 758-2400

08907635-080897

4/9

COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

(Page 2)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor MIYUKI ENOKIDA 1-00
Inventor's signature Miyuki Enokida
Date March 22, 1995 Citizen/Subject of JAPAN
Residence Yokohama-shi, Kanagawa-ken, Japan JPX
Post Office Address c/o Canon Kabushiki Kaisha
30-2, 3-chome, Shimomaruko, Ohta-ku, Tokyo, Japan

Full Name of Second Joint Inventor, if any TADASHI YOSHIDA 2-00
Second Inventor's signature T. Yoshida
Date March 22, 1995 Citizen/Subject of JAPAN
Residence Ichikawa-shi, Chiba-ken, Japan JPX
Post Office Address c/o Canon Kabushiki Kaisha
30-2, 3-chome, Shimomaruko, Ohta-ku, Tokyo, Japan

Full Name of Third Joint Inventor, if any _____
Third Inventor's signature _____
Date _____ Citizen/Subject of _____
Residence _____
Post Office Address _____

Full Name of Fourth Joint Inventor, if any _____
Fourth Inventor's signature _____
Date _____ Citizen/Subject of _____
Residence _____
Post Office Address _____

Full Name of Fifth Joint Inventor, if any _____
Fifth Inventor's signature _____
Date _____ Citizen/Subject of _____
Residence _____
Post Office Address _____

Full Name of Sixth Joint Inventor, if any _____
Sixth Inventor's signature _____
Date _____ Citizen/Subject of _____
Residence _____
Post Office Address _____